





NEW PRODUCT RELEASE

PIONEERS OF MULTI-MAT™



NEW SHOULDER MILLING INSERT – 4 CUTTING EDGES


NEW SHOULDER MILLING INSERT

4 CUTTING EDGES

LT 3130



LT 3000



ADVANTAGES

- 4 Cutting edges – Economic shoulder milling
- True and precise 90° – No mismatches after multiple passes
- Wiper flat – Optimized for better surface finishing

PRODUCT OVERVIEW

- Available in MAGIA and MAGIA PRO
- Available from diameter 25mm to 125mm
- Replaces 2-cutting edge inserts (e.g. APKT 10... APKT 16...)
- Not recommended for Helical Interpolation or Ramping Down

MAGIA PRO


DESIGNATION	GRADE	RADIUS (mm)	CUTTING EDGES	CUTTER LINE	MATERIAL RECOM-MENDATION	CATALOG #
ANKX 170608 PNTR	LT 3130	0.80	4	LT 787		M0004467

MAGIA

DESIGNATION	GRADE	RADIUS (mm)	CUTTING EDGES	CUTTER LINE	MATERIAL RECOM-MENDATION	CATALOG #
ANKX 170608 PNTR	LT 3000	0.80	4	LT 787		M0004025




PRODUCT RANGE



END MILL – ANKX 170608 PNTR

DESIGNATION	D	d	L	L1	Ap	Z	CATALOG #
LT 787 W-D-D025/2	25	25	44	100	12	2	M2001787
LT 787 W-W-D032/3	32	32	50	110	12	3	M2001789
LT 787 W-W-D040/4	40	32	50	115	12	4	M2001792



SHELL MILL – ANKX 170608 PNTR

DESIGNATION	D	d	L	Ap	Z	CATALOG #
LT 787 M-W-D040/4	40	16	40	12	4	M2001790
LT 787 M-W-D050/5	50	22	40	12	5	M2001793
LT 787 M-W-D063/6	63	22	40	12	6	M2001794
LT 787 M-W-D080/7	80	27	50	12	7	M2001795
LT 787 M-W-D0100/8	100	32	50	12	8	M2003825
LT 787 M-W-D0125/9	125	40	63	12	9	M2003826
LT 787 M-D-D160/10 *	160	40	63	12	10	M2003827

* ON REQUEST
Key: M2000602 Screw: M2000597


MAGIA PRO

CUTTING PARAMETERS



LAMINA TECHNOLOGIES

Side Milling up to 70%
ANKX 170608 PNTR



Material Group	Lamina Gr. N°	VDI	Material Examples	Hardness	Suggested Starting Parameters		Maximum Values			
					D.O.C (Ap) [mm]	Feed rate [mm/z]	D.O.C (Ap) [mm]	MAX. Feed Rate [mm/z]	MAX. D.O.C (Ap) [mm]	Feed Rate [mm/z]
Non Alloyed <										

For slot milling: Reduce the feed rate to 60%.
Max feed rate after chip thickness compensation = 0.8mm/tooth.
Not recommended for Ramping Down or Helical Interpolation.
Minimum recommended feed rate for side milling (Width of Cut up to 70%) = 0.12mm/tooth.
Cutting parameters recommended for stable part clamping and short tool/cutter overhang.
Must be reduced in case of vibrations.




Lamina Technologies is a Swiss manufacturer of carbide cutting tools specializing in milling and turning inserts made of state-of-the-art sub-micron grades and coatings by our team of specialists in our factory in Switzerland.

With the Multi-Mat™ concept, Lamina Technologies provides products that machine multiple materials with the same insert, thus allowing you to increase flexibility as well as reduce stock of unused and redundant cutting tools, allowing you to reduce the cost of production and increase production efficiency.

- Simplify your process
- Decrease your tooling costs
- Minimize your machining down time
- Increase your production efficiency

Lamina continues its fast pace worldwide expansion and is currently represented in over 32 countries.



LAMINA
TECHNOLOGIES

HEADQUARTERS

Lamina Technologies SA Switzerland

Rue Pythagore, 2
1400 Yverdon-les-Bains
Switzerland
T. +41 (0)24 423 55 55
F. +41 (0)24 423 54 44
info@lamina-tech.ch
www.lamina-tech.ch

SUBSIDIARIES

Lamina Technologies Deutschland GmbH

Athenslebener Weg 33
39418 Staßfurt
Germany
T. +49 (3925) 329 277
F. +49 (3925) 329 278
info@lamina-tech.de
www.lamina-tech.ch

Lamina Technologies do Brasil Ltda.

Avenida Macuco, 726 Cj
1603/1604, 04523-001
Moema, São Paulo
Brazil
T. +55 11 2344 7890
F. +55 11 2344 7888
info@lamina-tech.ch
www.lamina-tech.ch

Lamina Teknolojileri Kesici Takımlar

Cihangir Mahallesi, Petrol
Ofisi Caddesi
Şehit Komando Onbaşı Uğur
Hancı Sokak No. 5
Avcılar, İstanbul
Turkey 34310
T. +90 212 292 09 21
F. +90 212 292 59 51
info@lamina-tech.ch
www.lamina-tech.ch

Lamina Technologies France

15 Rue Bernard Palissy
Entrepot Jeantet STJ
25300 Granges Narboz
France
T./F. +33 (0) 381 49 67 30
info@lamina-tech.fr
www.lamina-tech.ch

Lamina Technologii LLC Russia

Kantemirovskaya str. 58
Office 6023
115477 Russia, Moscow
T./F. +7 499 653 93 56
info@lamina-russia.ru
www.lamina-tech.ch

Lamina Trading (Shanghai) Co., Ltd

Room 340, Building No.1
No. 526 Fute 3rd Road East
Pilot Free Trade Zone
200131 Shanghai
China
T. +86 21 22876501
info-cn@lamina-tech.ch
www.lamina-tech.ch