

DORMER  **PRAMET**

SCARFING

2020



CONTENTS

FEATURES AND BENEFITS

 4

NAVIGATOR

 9

INSERTS

 10

CUTTING RINGS

 16

HOLDERS

 18

TECHNICAL INFORMATION

 21





SCARFING

TOOLS FOR EXTERNAL AND INTERNAL TUBE WELD SCARFING

We offer an assortment of tools for processing welded pipes, known as scarfing. Our range is made up of tough coated cemented carbide inserts suitable for handling extreme heat. The geometry of the cutting edge provides excellent tube surface quality, increasing tool life.

We have recently added to our scarfing range with a new positive insert for external weld bed removal. Also, our existing assortment has been expanded with additional sizes of inserts, rings and spare parts to further meet your needs.

OUR OFFER

- Inserts for removal of weld bed from outside of tube diameter in a wide range of geometries and radii
- Rings for internal diameter scarfing in a wide range of sizes and grades
- Toolholders for external scarfing


BENEFITS

- **High quality surface finish** – due to cutting edge accuracy
- **Prolonged tool life** - grades with very good thermal and chipping resistance
- **Versatile** - Available in grades 6640 and T9335
- **Operation reliability** - stable clamping eliminates insert vibration

INSERT TYPES



SNMX 15, 19, 25



SNMX 2512, 1507



SNMA 1506, 2509



SPUB




LDGN



PSR

NEW ITEMS


NEW



SPUB 19

- Positive single-sided inserts with 11° clearance angle
- Four cutting edges


NEW



SNMX 1507

- Negative, double sided inserts
- Eight cutting edges and concave top


NEW



SNMA 1506

- Negative, double sided inserts
- Eight cutting edges and flat top

NEW




SNU


- Shims allow clamping of inserts SNMX 2512 and SNMX 1507, with concave top, into our current holders.

SCARFING


TOOLS FOR EXTERNAL AND INTERNAL TUBE WELD SCARFING



WHAT INSERT SHOULD I USE FOR MY TUBE DIAMETER ?



1 LDGN					
	L	3 S	B	GAN	
13,05	2.362	.197	.591	30°	



		ISO		P	M	K	N	S	H	PFRAD	
		LDGN 130560-R25	6640	■	■					.985	1.340-1.770
		LDGN 130560-R30	6640	■	■					1.180	1.615-2.125
		LDGN 130560-R35	6640	■	■					1.380	1.890-2.480
		LDGN 130560-R40	6640	■	■					1.575	2.125-2.835
4	5	LDGN 6 130560-R45	7 6640				8			9	10 2.190

1	Designation of insert type (group)
2	Schematic drawing of insert
3	Table with insert sizes [mm]
4	Icons - specific features, cutting edge type and picture of representative insert
5	Profile of main cutting edge

6	ISO code of insert
7	Grade
8	Application area of insert
9	Radius
10	Tube diameter


ICONS AND SYMBOLS

 Priority use

 Icon absence - tool is not recommended for specific operation or group of materials or it does not have specific feature

 Possible use






Icons - scarfing holders

General features of tools	
	Material groups
	Medium machining – good surface quality
	Unstable working conditions
	Very unstable working conditions
	External scarfing
	Internal scarfing



Icons and symbols - inserts

Features	
	Universal wide range option
	For tough materials (long chipping)
	Rounded edge
Conditions of use	
	Main application
	Secondary application
	Stable working conditions
	Unstable working conditions
	Very unstable working conditions

NAVIGATOR - ISO INSERTS

SNMX 15-R   10	SNMX 19-R   11	SNMX 25-R   12	SNMX 1507-R   12	SNMX 2512-R   13
SNMA 1506-R   14	SNMA 2509-R   15			
SPUB 19-R   15				
LDGN   16				
PSR   16-17				


NAVIGATOR - TOOLS

PFXN(RL) EXT		SN..
		 15 19 25
		25x25 32x32
	 18	 10-15
XLCD(N) EXT		LDGN
		 13
		25x25
	 19	 16


SNMX 15-R

PRAMET

	L	IC	D1	S
SNMX 15	.625	.625	.203	.321




i		ISO		P	M	K	N	S	H	PFRAD	ODW
		SNMX 15-R00	T9335	■	■					0	0-0
		SNMX 15-R07	T9335	■	■					.275	.395-.510
			6640	■	■					.275	.395-.470
		SNMX 15-R09	T9335	■	■					.355	.470-.630
			6640	■	■					.355	.470-.630
		SNMX 15-R11	T9335	■	■					.435	.590-.750
			6640	■	■					.435	.590-.750
		SNMX 15-R13	T9335	■	■					.510	.710-.905
			6640	■	■					.510	.710-.905
		SNMX 15-R15	T9335	■	■					.590	.785-1.065
			6640	■	■					.590	.785-1.065
		SNMX 15-R18	T9335	■	■					.710	.945-1.260
			6640	■	■					.710	.945-1.260
		SNMX 15-R20	T9335	■	■					.785	1.065-1.415
			6640	■	■					.785	1.065-1.415
		SNMX 15-R22	T9335	■	■					.865	1.180-1.535
			6640	■	■					.865	1.180-1.535
		SNMX 15-R25	T9335	■	■					.985	1.340-1.770
			6640	■	■					.985	1.340-1.770
		SNMX 15-R27	T9335	■	■					1.065	1.455-1.890
			6640	■	■					1.065	1.455-1.890
		SNMX 15-R30	T9335	■	■					1.180	1.615-2.125
			6640	■	■					1.180	1.615-2.125
		SNMX 15-R35	T9335	■	■					1.380	1.890-2.480
			6640	■	■					1.380	1.890-2.480
		SNMX 15-R40	T9335	■	■					1.575	2.125-2.835
			6640	■	■					1.575	2.125-2.835
		SNMX 15-R45	T9335	■	■					1.770	2.400-3.190
			6640	■	■					1.770	2.400-3.190
		SNMX 15-R50	T9335	■	■					1.970	2.675-3.545
			6640	■	■					1.970	2.675-3.545
		SNMX 15-R60	T9335	■	■					2.360	3.505-4.410
			6640	■	■					2.360	3.505-4.410
		SNMX 15-R90	6640	■	■					3.545	5.235-6.655




SNMX 19-R

PRAMET

	L	IC	D1	S
SNMX 19	.750	.750	.313	.321




i		ISO		P	M	K	N	S	H	PFRAD	ODW
		SNMX 19-R00	T9335	■	■					0	0-0
		SNMX 19-R10	T9335	■	■					.395	.550-.710
			6640	■	■					.395	.550-.710
		SNMX 19-R12	T9335	■	■					.470	.630-.825
			6640	■	■					.470	.630-.825
		SNMX 19-R15	T9335	■	■					.590	.785-1.065
			6640	■	■					.590	.785-1.065
		SNMX 19-R18	T9335	■	■					.710	.945-1.260
		SNMX 19-R20	T9335	■	■					.785	1.065-1.415
			6640	■	■					.785	1.065-1.415
		SNMX 19-R22	T9335	■	■					.865	1.180-1.535
		SNMX 19-R25	T9335	■	■					.985	1.340-1.770
			6640	■	■					.985	1.340-1.770
		SNMX 19-R30	T9335	■	■					1.180	1.615-2.125
			6640	■	■					1.180	1.615-2.125
		SNMX 19-R35	T9335	■	■					1.380	1.890-2.480
			6640	■	■					1.380	1.890-2.480
		SNMX 19-R40	T9335	■	■					1.575	2.125-2.835
			6640	■	■					1.575	2.125-2.835
		SNMX 19-R45	T9335	■	■					1.770	2.400-3.190
			6640	■	■					1.770	2.400-3.190
		SNMX 19-R50	T9335	■	■					1.970	2.675-3.545
			6640	■	■					1.970	2.675-3.545
		SNMX 19-R55	T9335	■	■					2.165	3.190-4.055
			6640	■	■					2.165	3.190-4.055
		SNMX 19-R60	T9335	■	■					2.360	3.505-4.410
			6640	■	■					2.360	3.505-4.410
		SNMX 19-R65	T9335	■	■					2.560	3.780-4.805
			6640	■	■					2.560	3.780-4.805
		SNMX 19-R75	T9335	■	■					2.955	4.370-5.550
		SNMX 19-R80	T9335	■	■					3.150	4.645-5.905
			6640	■	■					3.150	4.645-5.905
		SNMX 19-R85	T9335	■	■					3.345	4.960-6.260
		SNMX 19-R90	T9335	■	■					3.545	5.235-6.655
			6640	■	■					3.545	5.235-6.655



SNMX 25-R



	L	IC	D1	S
SNMX 25	1.000	1.000	.359	.480




i		ISO		P	M	K	N	S	H	PFRAD	QDW
		SNMX 25-R00	T9335	■	■					0	0-0
		SNMX 25-R50	T9335	■	■					1.970	2.625-3.500
		SNMX 25-R80	T9335	■	■					3.150	2.625-3.501
			6640	■	■					3.150	2.625-3.502
		SNMX 25-R100	T9335	■	■					3.935	2.625-3.503
			6640	■	■					3.935	2.625-3.504
		SNMX 25-R120	T9335	■	■					4.725	2.625-3.505
			6640	■	■					4.725	2.625-3.506
		SNMX 25-R140	T9335	■	■					5.510	2.625-3.507
			6640	■	■					5.510	2.625-3.508
		SNMX 25-R160	T9335	■	■					6.300	2.625-3.509
			6640	■	■					6.300	2.625-3.510
		SNMX 25-R180	T9335	■	■					7.085	2.625-3.511
		SNMX 25-R200	T9335	■	■					7.875	2.625-3.512
			6640	■	■					7.875	2.625-3.513

SNMX 1507-R



	L	IC	D1	S
1507	.625	.625	.203	.305




i		ISO		P	M	K	N	S	H	PFRAD	QDW
		SNMX 150708-R09	6640	■	■					.355	.510-.630
		SNMX 150708-R11	6640	■	■					.435	.630-.750
		SNMX 150708-R13	6640	■	■					.510	.750-.905
		SNMX 150708-R15	6640	■	■					.590	.865-1.065
		SNMX 150708-R18	6640	■	■					.710	1.025-1.260
		SNMX 150708-R20	6640	■	■					.785	1.140-1.415
		SNMX 150708-R22	6640	■	■					.865	1.260-1.535
		SNMX 150708-R25	6640	■	■					.985	1.455-1.770
		SNMX 150708-R27	6640	■	■					1.065	1.535-1.890
		SNMX 150708-R30	6640	■	■					1.180	1.730-2.125

SNMX 2512-R

PRAMET

	L	IC	D1	S
2512	1.000	1.000	.361	.472




			ISO		P	M	K	N	S	H	PFRAD	
   		SNMX 251224-R00	T9335	■	■						0	0-0
		SNMX 251224-R25	T9335	■	■						1.970	1.375-1.750
		SNMX 251224-R30	T9335	■	■						3.150	1.625-2.125
		SNMX 251224-R35	T9335	■	■						3.150	1.875-2.500
		SNMX 251224-R40	T9335	■	■						3.935	2.125-2.875
		SNMX 251224-R55	T9335	■	■						3.935	3.250-4.000
		SNMX 251224-R80	T9335	■	■						4.725	4.625-5.875
		SNMX 251224-R100	T9335	■	■						4.725	5.875-7.375
		SNMX 251224-R120	T9335	■	■						5.510	7.000-8.875

SNMA 1506-R



	L	IC	D1	S
1506	.625	.625	.203	.250




i		ISO		P	M	K	N	S	H	PFRAD	ODW
	SNMA 150608-R09	6640								.355	.510-.630
	SNMA 150608-R11	6640								.435	.630-.785
	SNMA 150608-R13	6640								.510	.750-.945
	SNMA 150608-R15	6640								.590	.865-1.100
	SNMA 150608-R18	6640								.710	1.065-1.300
	SNMA 150608-R20	6640								.785	1.180-1.455
	SNMA 150608-R22	6640								.865	1.300-1.615
	SNMA 150608-R25	6640								.985	1.455-1.850
	SNMA 150608-R27	6640								1.065	1.575-1.970
	SNMA 150608-R30	6640								1.180	1.730-2.205
	SNMA 150608-R35	6640								1.380	2.045-2.560
	SNMA 150608-R40	6640								1.575	2.325-2.955
	SNMA 150608-R42	6640								1.655	2.440-3.070
	SNMA 150608-R45	6640								1.770	2.640-3.305
	SNMA 150608-R50	6640								1.970	2.915-3.700
	SNMA 150608-R60	6640								2.360	3.505-4.410
	SNMA 150608-R65	6640								2.560	3.780-4.805
	SNMA 150608-R70	6640								2.755	4.095-5.155
	SNMA 150608-R75	6640								2.955	4.370-5.550
	SNMA 150608-R80	6640								3.150	4.645-5.905
	SNMA 150608-R90	6640								3.545	5.235-6.655
	SNMA 150608-R105	6640								4.135	6.100-7.755
	SNMA 150608-R120	6640								4.725	7.010-8.860

SNMA 2509-R

PRAMET

	L	IC	D1	S
2509	1.000	1.000	.359	.375




i		ISO		P	M	K	N	S	H	PFRAD	
		SNMA 250924-R00	T9335							0	0-0
		SNMA 250924-R60	T9335							2.360	3.505-4.410

SPUB 19-R

PRAMET

	L	IC	D1	S
SPUB 19	.750	.750	.203	.187




i		ISO	ANSI		P	M	K	N	S	H	PFRAD	
		SPUB 19-R00 *	SPUB-63-M	T9335							0	0-0
				6640							0	0-0
		SPUB 19-R12	SPUB-63-B	T9335							.470	.710-.865
				6640							.470	.710-.865
		SPUB 19-R15	SPUB-63-C	T9335							.590	.865-1.100
				6640							.590	.865-1.100
		SPUB 19-R20	SPUB-63-D	T9335							.785	1.140-1.455
				6640							.785	1.140-1.455
		SPUB 19-R25	SPUB-63-E	T9335							.985	1.455-1.850
				6640							.985	1.455-1.850
		SPUB 19-R30	SPUB-63-F	T9335							1.180	1.770-2.245
				6640							1.180	1.770-2.245
		SPUB 19-R40	SPUB-63-G	T9335							1.575	2.360-2.990
				6640							1.575	2.360-2.990
		SPUB 19-R50	SPUB-63-H	T9335							1.970	2.955-3.740
				6640							1.970	2.955-3.740
		SPUB 19-R63	SPUB-63-I	T9335							2.480	3.740-4.725
				6640							2.480	3.740-4.725

* This insert has 11° positive clearance all around.

LDGN




	L	S	B	GAN
13,05	2.362	.197	.591	30°



i		ISO		P	M	K	N	S	H	PFRAD	ODW
		LDGN 130560-R25	6640							.985	1.340-1.770
		LDGN 130560-R30	6640							1.180	1.615-2.125
		LDGN 130560-R35	6640							1.380	1.890-2.480
		LDGN 130560-R40	6640							1.575	2.125-2.835
		LDGN 130560-R45	6640							1.770	2.400-3.190

PSR



i	ISO		P	M	K	N	S	H	INSD	CDI	S	PFRAD	ODW
	PSR0-R3.5	T9335							.236	.118	.138	.135	.470-.530
	PSR0-R4	T9335							.236	.138	.138	.155	.470-.550
	PSR0-R4.5	T9335							.315	.157	.157	.180	.530-.750
		5040							.315	.157	.157	.180	.530-.750
		S45							.315	.157	.157	.180	.530-.750
	PSR0/10-R4.5*	T9335							.394	.157	.157	.180	.530-.750
	PSR0-R5.5	T9335							.315	.197	.157	.225	.630-.785
		5040							.315	.197	.157	.225	.630-.785
	PSR0/10-R5.5*	T9335							.394	.197	.157	.225	.630-.785
	PSR0-R6	T9335							.394	.217	.177	.250	.670-.785
		5040							.394	.217	.177	.250	.670-.785
	PSR0-R6.5	T9335							.394	.236	.177	.270	.670-.825
		5040							.394	.236	.177	.270	.670-.825
		S45							.394	.236	.177	.270	.670-.825
	PSR0-5-R6.5*	T9335							.394	.236	.197	.270	.670-.865
	PSR0-R7	T9335							.394	.256	.177	.290	.670-.865
		S45							.394	.256	.177	.290	.785-.865

	ISO								INSD	CDI	S	PFRAD	
			P	M	K	N	S	H					
	PSR1-R7	T9335	■	■					.512	.236	.197	.270	.785-.865
		S040	■						.512	.236	.197	.270	.785-.865
		S45	■						.512	.236	.197	.270	.785-.865
	PSR1-R7.5	T9335	■	■					.512	.268	.197	.305	.825-.905
	PSR1-R8	T9335	■	■					.512	.276	.197	.315	.865-.945
		S040	■						.512	.276	.197	.315	.865-.945
		S45	■						.512	.276	.197	.315	.865-.945
	PSR1-R9	T9335	■	■					.512	.315	.197	.360	.945-1.025
		S040	■						.512	.315	.197	.360	.985-1.100
		S45	■						.512	.315	.197	.360	.985-1.100
PSR1-R10	T9335	■	■					.512	.354	.197	.400	.985-1.100	
	S040	■						.512	.354	.197	.400	.985-1.100	
	S45	■						.512	.354	.197	.400	.985-1.100	
	PSR2-R9	T9335	■	■					.748	.315	.315	.360	.945-1.025
	PSR2-R10	T9335	■	■					.748	.354	.315	.400	1.025-1.100
		S040	■						.748	.354	.315	.400	1.025-1.100
		S45	■						.748	.354	.315	.400	1.025-1.100
	PSR2-R11	T9335	■	■					.748	.394	.315	.450	1.100-1.180
		S040	■						.748	.394	.315	.450	1.100-1.180
		S45	■						.748	.394	.315	.450	1.100-1.180
	PSR2-R12	T9335	■	■					.748	.433	.315	.490	1.180-1.340
		S040	■						.748	.433	.315	.490	1.180-1.340
		S45	■						.748	.433	.315	.490	1.180-1.340
PSR2-R13	T9335	■	■					.748	.469	.315	.530	1.220-1.380	
PSR2-R14	T9335	■	■					.748	.492	.315	.565	1.260-1.615	
	PSR3-R12	T9335	■	■					.866	.433	.394	.490	1.180-1.340
	PSR3-R14	T9335	■	■					.866	.472	.394	.540	1.260-1.615
		S040	■						.866	.472	.394	.540	1.260-1.615
		S45	■						.866	.472	.394	.540	1.260-1.615
	PSR3-R17	T9335	■	■					.866	.591	.394	.675	1.415-1.615
		S040	■						.866	.591	.394	.675	1.415-1.615
S45		■						.866	.591	.394	.675	1.415-1.615	
	PSR4-R20	T9335	■	■					1.181	.669	.472	.765	1.615-1.970
	PSR4-R23	T9335	■	■					1.181	.787	.472	.900	1.890-2.245
		S040	■						1.181	.787	.472	.900	1.890-2.245
		S45	■						1.181	.787	.472	.900	1.890-2.245
	PSR5-R25	T9335	■	■					1.378	.866	.472	.990	2.755-3.345
		S040	■						1.378	.866	.472	.990	2.755-3.345
S45		■						1.378	.866	.472	.990	2.755-3.345	
PSR5-R28	T9335	■	■					1.378	.984	.472	1.120	3.345-3.935	
	S040	■						1.378	.984	.472	1.120	3.345-3.935	
	S45	■						1.378	.984	.472	1.120	3.345-3.935	
	PSR6-R34	T9335	■	■					1.772	1.181	.591	1.345	3.935-5.120
		S040	■						1.772	1.181	.591	1.345	3.935-5.120
		S45	■						1.772	1.181	.591	1.345	3.935-5.120
	PSR7-R39	T9335	■	■					1.969	1.378	.591	1.555	4.920-5.510
		S45	■						1.969	1.378	.591	1.555	4.920-5.510
	PSR8-R46	T9335	■	■					2.165	1.575	.709	1.795	5.510-7.085
		S040	■						2.165	1.575	.709	1.795	5.510-7.085

* rings deviating from standard dimension






* INSD, S - modification

PXFN(RL)



PRAMET

P



	H	B	HF	WF	LF	LH	ALP	lbs			
	[in]	[in]	[in]	[in]	[in]	[in]	[°]				
PXFNR/L 2525 R 15	.984	.984	.984	.984	7.874	1.575	6	2.315	GI185	PX 40	AT009
PXFNR/L 2525 S 19	.984	.984	.984	.984	9.843	1.772	6	2.866	GI186	PX 50	-
PXFNR/L 3232 S 25	1.260	1.260	1.575	1.575	9.843	1.969	6	4.850	GI199	PX 60	AT010
PXFNR/L 2525 R 15/15	.984	.984	.984	.984	7.874	1.575	20	2.315	GI185	PX 40	AT009
PXFNR/L 2525 S 19/15	.984	.984	.984	.984	9.843	1.969	20	2.866	GI186	PX 50	-



GI185	SNMX 15-R..
GI186	SNMX 19-R..
GI199	SNMX 25-R..



PX40	SNU 150310-R	PU 03	US 36	6,0	M8x1	1.024	NT 05	MT 07	HXX 4
PX50	SNU 190410-R	PU 05	US 38	8,0	M10x1	1.142	NT 06	MT 06	HXX 5
PX60	SNU 250424-R	PU 06	US 47	8,0	M12x1	1.299	NT 08	MT 08	HXX 5





AT009	SNMX 150708-R..	SNU 150410-CX
AT010	SNMX 251224-R..	SNU 250524-CX

XLCDN

P M

PRAMET

P



	H	B	LF	LH	ALP	lbs	GI187	PX10
	[in]	[in]	[in]	[in]	[°]			
XLCDN 2525 R 15	.984	.984	7.874	1.969	6	2.425	GI187	PX10



GI187



LDGN 130560...



PX10



HS 0825




M8



.984



HKX 6




TECHNICAL INFORMATION

GRADES FOR SCARFING


Grade Identification	Area of Application	Application	Feed	Cutting speed	Resistance to adverse Working Conditions	Substrate	Coating	Colour	Coolant benefit	General purpose	High speed tube mills	Low speed tube mills
T9335	P20 - P45	■				FGM	MT-CVD		+++	✓	✓	
	M15 - M40	■										
6640	P20 - P45	■				H	MT-CVD		+++	✓		✓
	M15 - M40	■										
5040	P30 - P45	■				S	MT-CVD		++	✓		✓
	M30 - M40	□										
S45	P30 - P45	■				S	X		++			✓
	M30 - M40	□										

Substrate			Coating	
H	WC-Co based substrate		MT-CVD	Medium-temperature chemical method of coating
FGM	Functionally graded substrate		X	Uncoated grade
S	Substrate with cubic carbides			

PXFN(RL) - VARIOUS HOLDERS ACCORDING TO HEAD INCLINATION



LDGN – INSERTS SUITABLE FOR REGRINDING




Offers long tool life due to total length of insert (2.4 inch), which can be ground several times to a minimum length of 1 inch.

Rake angle GAN can be easily modified (more or less positive) by grinding the insert to optimize the scarfing process.

Suitable for small cross section of scarf.


PXFN(RL) - VARIOUS SPARE PARTS ACCORDING TO INSERT SHAPE



1	2	3	4	5	6	7	8
PXFNR/L 2525 R 15 PXFNR/L 2525 R 15/15							
			PU 03	US 36	NT 07	MT 07	HKX 4
PXFNR/L 2525 S 19 PXFNR/L 2525 S 19/15							
	SNMX 19-Rxx	SNU 190410-R	PU 05	US 38	NT 06	MT 06	HKX 5
PXFNR/L 3232 S 25							
	SNMX 25-Rxx	SNU 250424-R					
			PU 06	US 47	NT 08	MT 08	HKX 5

SCARFING RINGS - HOW TO CALCULATE WORKING RADIUS PFRAD

Working radius PFRAD circle of osculatory DCI



$$PFRAD = \frac{DCI}{2 \sin \beta}$$

DCI - internal rings diameter

β - angle of ring rotation

SIMPLY RELIABLE

As a professional you can judge the quality of work by just looking at the chip. Our chip is a clean and uncomplicated shape that in itself tells a story. It is a clear and consistent signal and that's why we use it as a symbol for being **Simply Reliable**.

Argentina

T: 54 (11) 6777-6777
F: 54 (11) 4441-4467
info.ar@dormerpramet.com

Austria

T: +31 10 2080 240
info.at@dormerpramet.com

Belgium & Luxembourg

T: +32 3 440 59 01
info.be@dormerpramet.com

Brazil

T: +55 11 5660 3000
info.br@dormerpramet.com

Canada

T: (888) 336 7637
En Français: (888) 368 8457
F: (905) 542 7000
cs.canada@dormerpramet.com

China

T: +86 21 2416 0508
info.cn@dormerpramet.com

Croatia

T: +385 98 407 489
info.hr@dormerpramet.com

Czech Republic

T: +420 583 381 111
F: +420 583 215 401
info.cz@dormerpramet.com

Denmark

T: 808 82106
info.se@dormerpramet.com

Finland

T: 0205 44 7003
info.fi@dormerpramet.com

France

T: +33 (0)2 47 62 57 01
F: +33 (0)2 47 62 52 00
info.fr@dormerpramet.com

Germany

T: +49 9131 933 08 70
F: +49 9131 933 08 742
info.de@dormerpramet.com

Hungary

T: +36-96 / 522-846
F: +36-96 / 522-847
info.hu@dormerpramet.com

India

T: +91 11 4601 5686
info.in@dormerpramet.com

Italy

T: +39 02 30 70 54 44
info.it@dormerpramet.com

Kazakhstan

T: +7 771 305 11 45
info.kz@dormerpramet.com

Mexico

T: +52 (555) 7293981
F: +52 (555) 7293981
cs.mexico@dormerpramet.com

Netherlands

T: +31 10 2080 240
info.nl@dormerpramet.com

Norway

T: 800 10 113
info.se@dormerpramet.com

Poland

T: +48 32 78-15-890
F: +48 32 78-60-406
info.pl@dormerpramet.com

Portugal

T: +351 21 424 54 21
info.pt@dormerpramet.com

Romania

T: +(0)730 015 885
info.ro@dormerpramet.com

Russia

T: +7 (495) 775 10 28
Φ: +7 (499) 763 38 90
info.ru@dormerpramet.com

Slovakia

T: +421 (41) 764 54 60
F: +421 (41) 763 74 49
info.sk@dormerpramet.com

Slovenia

T: +385 98 407 489
info.si@dormerpramet.com

Spain

T: +34 935717722
info.es@dormerpramet.com

Sweden

responsible for Iceland
T: +46 35 16 52 96
info.se@dormerpramet.com

Switzerland

T: +31 10 2080 240
info.ch@dormerpramet.com

Turkey

T: +90 533 212 45 47
info.tr@dormerpramet.com

Ukraine

T: +38 056 736 30 21
F: +38 067 220 97 48
info.ua@dormerpramet.com

United Kingdom

responsible for Ireland
T: 0870 850 4466
F: 0870 850 8866
info.uk@dormerpramet.com

United States of America

T: (800) 877-3745
F: (847) 783-5760
cs@dormerpramet.com

Other countries

South America

T: +55 11 5660 3000
info.br@dormerpramet.com

Adria

T: +420 583 381 527
F: +420 583 381 401
info.rcee@dormerpramet.com

Rest of the World

Dormer Pramet International UK
T: +44 1246 571338
F: +44 1246 571339
info.int@dormerpramet.com

Dormer Pramet International CZ

T: +420 583 381 520
F: +420 583 215 401
info.int.cz@dormerpramet.com